



规格	
压力角	20°
材料	C45
热处理	齿面高频淬火
齿部加工方式	磨削
精度等级	6h25
端部连接方式	可拼接安装

齿条号	模数	L	B	H	h	齿数	l	l1	l2	l3	b1	h1	d1	d2	d3	f	孔数	重量 (kg)
SR2-100GB	2	1005.30	24	24	22	160	942.70	31.3	125.66	62.8	7	8	7	11	5.7	2	8	4.20
SR2-200GB	2	2010.62	24	24	22	320	1948.00	31.3	125.66	62.8	7	8	7	11	5.7	2	16	8.40
SR3-100GB	3	1017.90	29	29	26	108	949.10	34.4	127.23	63.6	9	9	10	15	7.7	2	8	6.00
SR3-200GB	3	2035.75	29	29	26	216	1967.00	34.4	127.23	63.6	9	9	10	15	7.7	2	16	12.00
SR4-100GB	4	1005.30	39	39	35	80	930.30	37.5	125.66	62.8	9	12	10	15	7.7	3	8	10.50
SR4-200GB	4	2010.62	39	39	35	160	1935.60	37.5	125.66	62.8	9	12	10	15	7.7	3	16	21.00
SR5-050GB	5	502.60	49	49	34	32	442.40	30.1	125.66	62.8	13	12	14	20	11.7	3	4	6.70
SR5-100GB	5	1005.30	49	49	34	64	945.00	30.1	125.66	62.8	13	12	14	20	11.7	3	8	13.40
SR5-150GB	5	1507.96	49	49	34	96	1447.70	30.1	125.66	62.8	13	12	14	20	11.7	3	12	20.10
SR5-200GB	5	2010.62	49	49	34	128	1950.40	30.1	125.66	62.8	13	12	14	20	11.7	3	16	26.80
SR6-050GB	6	508.90	59	59	43	27	446.10	31.4	127.23	63.6	17	16	18	26	15.7	3	4	10.10
SR6-100GB	6	1017.80	59	59	43	54	955.00	31.4	127.23	63.6	17	16	18	26	15.7	3	8	20.20
SR6-150GB	6	1526.81	59	59	43	81	1464.00	31.4	127.23	63.6	17	16	18	26	15.7	3	12	30.30
SR6-200GB	6	2035.75	59	59	43	108	1973.00	31.4	127.23	63.6	17	16	18	26	15.7	3	16	40.40
SR8-050GB	8	502.65	79	79	71	20	449.45	26.6	125.66	62.8	21	25	22	33	19.7	3	4	22.38
SR8-100GB	8	1005.30	79	79	71	40	952.00	26.6	125.66	62.8	21	25	22	33	19.7	3	8	44.76
SR8-200GB	8	2010.61	79	79	71	80	1957.30	26.6	125.66	62.8	21	25	22	33	19.7	3	16	89.50
SR10-100GB	10	1005.30	99	99	89	32	753.96	125.66	125.66	62.83	32	32	33	48	19.7	3	8	68.72

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。