EX-SC-3840一体式地毯抽洗机 Self-Contained Extractor EX-SC-3840



一体式地毯抽洗机:流线型的外观设计,可靠的清洁性能。

本款地毯抽洗机可轻松去除顽固污渍,同时不会损伤周围设施,清洁效果出众。符合人体工程力学的手柄以及一键式控制装置,最大程度地简化了操作过程中的手动工作,可实现连续数小时的舒适操作。刷子高度可调节,操作人员可根据需要,选择最合适的刷子高度。

机身结构经久耐用,清洁性能可靠

机身采用经久耐用的聚乙烯材料,可在凹凸不平的地面和有裂缝的地面 轻松移动,机体经久耐用,满足各种日常地毯抽洗工作的需求。

操作更灵活

本款抽洗机非常适合清洗狭窄的区域,比如教室、办公楼、医院、饭店,同时也能清洗更大型的开阔场所。

Sleek design and reliable performance in a self contained carpet extractor.

This carpet extractor allows for the exact amount of agitation to remove tough soil without causing damage. The ergonomic handle grip and solution controls minimize hand movement during operation and allow for hours of comfortable operation. The adjustable brush allows the operator to choose the optimal brush height.

Durable construction, reliable performance

Constructed of durable polyethylene that resists dents and cracks, this extractor is built to last and can withstand the demands of everyday extracting.

Greater maneuverability

This extractor is perfect for cleaning in confined areas like classrooms, office buildings, hospitals and restaurants as well as larger open areas.

主要优势 Key Benefits

- 刷头盖板设有大功率马达、硬质刷毛以及两个喷嘴,具有出众的清洁性能。
- Brush scrub deck with large motor and stiff brush coupled with dual spray nozzles provide outstanding cleaning performance
- 手柄符合人体工程学设计并且 采用一键式控制装置,操作舒 适。
- Ergonomic handle and one button solution control allows for comfortable operation
- 机身轻便、结构坚固耐用并且 在机身中央设有低底盘重力轮 胎系统、机身移动极为方便。
- This unit moves easily with its lightweight yet durable construction and low center of-gravity bladder system





EX-SC-3840一体式地毯抽洗机 Self-Contained Extractor EX-SC-3840



产品特点 Features	产品规格* Specifications*
产品名称 Product Name	EX-SC-3840
真空系统 Vacuum System 真空马达马力 Vacuum motor HP 真空马达级数 Vacuum motor stages 真空水位提升 Water lift at sealed orifice 2 in / 50 mm孔径的气流 Airflow through 2 in / 50 mm orifice 真空传输槽 Vacuum shoe size	1.8 hp / 1.4 kW 2 stage 3480 mm / 137 in 101 cfm / 2.89 m ³ 20 in /510 mm
污水系统 Recovery System 污水箱容量 Recovery tank capacity 污水箱类型 Recovery tank description	14.5 gal /55 L 集成气囊式水箱 Integrated bladder tank
刷子驱动系统 Brush Drive System 刷子马达电流 Brush motor amp 刷子每分钟转速 Brush RPM 刷子马达每分钟转速 Brush motor RPM 刷子宽度 Brush width 刷毛类型 Brush bristle type	0.5 A 1200 2100 14 in / 406 mm 尼龙材质,四排刷毛,呈360度螺旋型排列 Nylon construction, four rows of bristles arranged with 360 degrees spiral
清水系统 Solution System 清水泵电流 Solution pump amps 清水泵压力 Solution pump pressure 清水泵电压 Solution pump voltage 清水箱容量 Solution capacity 电磁阀 Solenoid valve 喷嘴 Spray jets	1 A 100 psi / 7 Bar 230 / 240 V 10 gal / 38 L 电动式 Electric 直角转弯,快速拆卸式 Quarter turn, quick disconnect
总耗电量 Total Power Consumption	6.5 A / 1.64 kW
电线 Power Cord 电线长度 Power cord length 电线类型 Power cord type	15 ft / 4.57 m 16规格 16 gauge
可选配零件 Optional Accessories	各种吸管、手动工具、清水软管和污水软管等 Various wands, hand tools, solution and recovery hoses, etc.
尺寸/重量/噪音等级 Dimensions/Weight/Sound Level 长度/宽度/高度/重量/噪音级别 Length/Width/Height/Weight/Sound	长度: 43 in / 1092 mm, 宽度: 16 in / 406 mm, 高度: 34 in / 864 mm, 重量: 89 lb / 42 kg, >70dBA(工作噪音) L: 43 in / 1092 mm, W: 16 in / 406 mm, H: 34 in / 864 mm, Wt: 89 lb / 42 kg, >70 dBA (@ operator's ear)
质量保证 Warranty	若需获取完整的保修详情,请咨询您的销售代表或授权经销商。 See your sales representative or authorized distributor for complete warranty details.

授权代理商

Seeing is Believing 眼见为实

如需了解更多坦能公司的产品, 技术和解 决方案, 请发邮件至 tennantchina@tennantco.com

坦能清洁系统设备(上海)有限公司

坦能亚太及中国总部

Tennant APAC and China Headquater

Tennant Cleaning Systems & Equipment(Shanghai)Co., Ltd. 地址:上海市青浦区白鹤镇漕盈路3777号1幢 邮编: 201712

Add: Building 1, 3777 Cao Ying Road, Baihe Town, Qingpu District, Shanghai, China, 201712 电话Tel: (86 21) 6922 5333

传真Fax: (86 21) 6922 5262 销售热线Sales hotline: 800 820 2366 服务热线Service hotline: 400 820 0885

坦能始终致力于其产品的改进。基于该原因,如有技术更改,恕不通知, 版权所有, 未经许可不得翻印 09/2011